

Charging Time For Slide Lithium-ion Batteries

Battery					Charger					
Voltage	Image	Type	Capacity	Cooling Windows	UC12SL	UC18YKSL	UC18YFSL*1	UC18YSL3*1	UC18YML2*1 (AC / DC)*2	UC36YSL*1
10.8 - 12V Peak		BSL1215	1.5Ah	-	60min	-	-	-	-	-
		BSL1225M	2.5Ah	-	37min	-	-	-	-	-
		BSL1240M	4.0Ah	-	22min	-	-	-	-	-
14.4V		BSL1415	1.5Ah	●	-	40min	22min	15min	22 / 60min	15min
		BSL1420*3	2.0Ah	●	-	60min	30min	20min	30 / 80min	20min
		BSL1425*3	2.5Ah	●	-	75min	35min	25min	35 / 100min	25min
		BSL1430C*3	3.0Ah	●	-	90min	45min	30min	45 / 120min	30min
		BSL1430*3	3.0Ah	●	-	90min	45min	20min	45 / 120min	30min
		BSL1440*3	4.0Ah	●	-	120min	60min	26min	60 / 160min	40min
		BSL1450*3	5.0Ah	●	-	150min	75min	32min	75 / 200min	50min
		BSL1460	6.0Ah	●	-	180min	90min	38min	90 / 240min	60min
18V		BSL1815	1.5Ah	●	-	40min	22min	15min	22 / 60min	15min
		BSL1820M	2.0Ah	●	-	60min	30min	20min	30 / 80min	20min
		BSL1820*3	2.0Ah	●	-	60min	30min	20min	30 / 80min	20min
		BSL1825*3	2.5Ah	●	-	75min	35min	25min	35 / 100min	25min
		BSL1830C	3.0Ah	●	-	90min	45min	30min	45 / 120min	30min
		BSL1830*3	3.0Ah	●	-	90min	45min	20min	45 / 120min	30min
		BSL1840*3	4.0Ah	●	-	120min	60min	26min	60 / 160min	40min
		BSL1840M	4.0Ah	●	-	120min	60min	40min	60 / 160min	40min
		BSL1850	5.0Ah	●	-	150min	75min	32min	75 / 200min	50min
		BSL1850C	5.0Ah	●	-	150min	75min	32min	35min	50min
		BSL1850MA	5.0Ah	●	-	150min	75min	32min	75 / 200min	50min
		BSL1860*3	6.0Ah	●	-	180min	90min	38min	90 / 240min	60min
25.2V		BSL2530	3.0Ah	●	-	-	-	-	-	30min
36V		BSL36C18	1.5Ah	●	-	-	-	20min	-	-
		BSL3625*3	2.5Ah	●	-	-	-	-	-	25min
		BSL36A18	2.5Ah	●	-	-	-	32min	-	-
		BSL3626*3	2.6Ah	●	-	-	-	-	-	25min
		BSL36B18	4.0Ah	●	-	-	-	52min	-	-
		BL36200	21Ah	-	-	-	-	-	-	3hrs.

*1. With cooling fan. *2. Two-way AC/DC charger usable with in-car power source. *3. Discontinued battery.

For Cassette Lithium-ion Batteries

Battery					Charger							
Voltage	Image	Type	Capacity	Cooling Windows	UC3SFL	UC3SML (AC / DC)*2	UC7SL	UC10SL2	UC18YKL	UC18YGL2	UC18YRL*1	UC18YG
3.6V		EBM315	1.5Ah	-	30min	60 / 60min	-	-	-	-	-	-
7.2V		BCL715	1.5Ah	-	-	-	30min	-	-	-	-	-
		BCL715G	1.5Ah	-	-	-	-	-	-	-	-	30min
10.8V		BCL1015S*3	1.3Ah	-	-	-	-	25min	-	-	-	-
		BCL1015*3	1.5Ah	-	-	-	-	30min	-	-	-	-
		BCL1030C	3.0Ah	-	-	-	-	60min	-	-	-	-
		BCL1030*3	3.0Ah	-	-	-	-	60min	-	-	-	-
		BCL1030M*3	3.0Ah	-	-	-	-	60min	-	-	-	-
14.4V		BCL1415*3	1.5Ah	●	-	-	-	-	60min	40min	20min	-
		BCL1420*3	2.0Ah	●	-	-	-	-	80min	60min	30min	-
		BCL1430*3	3.0Ah	●	-	-	-	-	120min	90min	45min	-
		BCL1440*3	4.0Ah	●	-	-	-	-	160min	120min	60min	-
18V		BCL1815*3	1.5Ah	●	-	-	-	-	60min	40min	20min	-
		BCL1820*3	2.0Ah	●	-	-	-	-	80min	60min	30min	-
		EBM1830*3	3.0Ah	●	-	-	-	-	120min	90min	45min	-
		BCL1840*3	4.0Ah	●	-	-	-	-	160min	120min	60min	-

*1. With cooling fan. *2. Two-way AC/DC charger usable with in-car power source. *3. Discontinued battery.

Refer to instruction manuals of the HiKOKI chargers for charging time for other HiKOKI batteries.