

Cordless Disc Grinder


18V - 5.0Ah 115mm / 125mm G 18DSL2



Extremely Easy to Use

1 Improved Overload **Durability**

The G18DSL2 cordless disc grinder achieves 1.6 times higher overload durability than our conventional model owing to an optimized gear ratio and bigger motor fan for higher burnout resistance.



Overload durability: Comparisons of torques when the motors burn out when the durability index of the previous model is considered 100. (The values are for reference. They vary based on various conditions.)

3 Soft Grip Handle

4 Anti-Restart Protection

5 Remaining Battery Indicator

Cordless Disc Grinder



Specifications

specifications			
Model		G 18DSL2	
Capacity	Wheel Dia.	115mm	125mm
	Hole Dia.	22.23mm	
	Thickness	6mm	
Spindle Thread		M14 x 2	
Battery Voltage		18V	
No Load Speed		9,000/min	
Overall Length		306mm	
Weight* ³		2.1kg (with BSL1850C) / 2.6 kg (with BSL36B18)*4	
Standard Accessories*5		2 Batteries (BSL1850C), Charger (UC18YFSL), Depressed Center Wheel, Wrench, Side Handle, Wheel Guard, Battery Cover, Carrying Case	

*1. Vs. HiKOKI's G18DSL cordless disc grinder.

*2. With BSL1850C battery. The values shown are for reference purposes and may vary according to the workpiece materials and other operating conditions.

*3. Weight: according to EPTA-Procedure 01/2014.

*4. Sold separately.

*5. Standard accessories vary by country or area

Distributed by:

2 Compact and Lightweight **Design with a Small Grip**



The lightweight and compact body with a small grip diameter offers easy handling and fatigue-less operation, especially in narrow spaces.

Runtime per Charge*2 (with BSL1850C Battery)

Concrete Scoring Rebar Cutting (Ф10mm) (5mm in depth) Approx. Approx Cuts

HiKOKI