Cordless Work Lights

18V UB 18DB







|Remaining Battery Indicator

Available with all models: UB18DB, UB18DC, UB18DD The onboard battery indicator light displays the remaining charge.



Note: Depending on the battery condition and operating environment, the actual remaining battery charge may not match what is displayed on the remaining battery indicator. When UB18DD is used with a power cord, the indicator light remains off.

Indicator Light

....

Battery Charge

Remaining

Over 80%

60% - 80%

40% - 60% 20% - 40%

Below 20%

Dust and Water Resistant

The UB18DB, UB18DC, and UB18DD are IP54 / IP65 / IP65-compliant respectively under the following conditions.


UB 18DB	IP54	When the battery cover is closed.
UB 18DC	IP65 When the battery cover and rubber USB port cover are closed.	
UB 18DD	IP65	When the battery cover, rubber USB port cover, and rubber AC socket cover are closed.

The dust and water resistant products are designed to withstand the effects of dust and water, but there is no guarantee that they will not malfunction. Do not use or leave them in locations where they are subjected to excessive amounts of dusts, submerged in water, or subjected to rainwater. (Only the main units conform to each protection class rating when equipped with batteries.)

Specifications			
Model	UB 18DB	UB 18DC	UB 18DD
Battery Voltage	18V		
Brightness Adjustment Range	350 - 2,000lm	700 - 4,000lm	1,000 - 10,000lm
LED (White)	1рс.	60pcs.	216pcs.
USB Port	-	5V, 1A	5V, 1A
Dimensions (L x W x H)	163 x 142 x 209mm	186 x 155 x 276mm	148 x 314 x 323mm
Weight	1.2kg (Without Battery)	1.9kg (Without Battery)	4.1kg (Without Battery and Power Cord)
Standard Accessories*	-	-	Power Cord, Adapter

* Standard accessories vary by country or area.

Distributed by:



Koki Holdings Co., Ltd.

Hikoki **UNLEASH the NEXT**





Cordless Work Lights

18V	UB	18DB
18V	UB	18DC
18V	UB	18DD

3 Models with Adjustable Brightness to Suit Your Needs





UB 18DC

UB 18DB

Compact, Lightweight, and **Easy to Use in Small Spaces**

Up to

2,000Im

IP54

Dust and Water

Resistant

Continuous Runtime per Charge*1

Max. Brightness

2,000lm Approx. **3.2h**

Approx. 5.5h

Approx. **9.0h**

Min.

Brightness

350lm

Approx

19h Approx. 32h

Approx. 51h

18V

Battery

3.0Ah

5.0Ah

8.0Ah

UB 18DB

Suitable for Equipment Installation Work in a Dark Building

HIKOKI

UB 18DC



Adjustable from 700lm to 4,000lm.



4,000lm	Continuous Runtime per Charge*1			
	18V Battery	Min. Brightness 700lm	Max. Brightness 4,000lm	
	3.0Ah	Approx. 12h	Approx. 1.5h	
	5.0Ah	Approx. 20h	Approx. 3.0h	
	8.0Ah	Approx. 30h	Approx. 4.5h	



N. C. L.	18V Battery	Min. Brightness 700lm	Max. Brightness 4,000lm
	3.0Ah	Approx. 12h	Approx. 1.5h
1	5.0Ah	Approx. 20h	Approx. 3.0h
	8.0Ah	Approx. 30h	Approx. 4.5h



Up to **IP65 Dust and Water** Resistant







360

Adjustable from 350lm to 2,000lm.

*1. Runtime per charge may vary according to types of batteries and operating conditions. *2. Ensure the unit is securely hung.

Ηί ΚΟΚΙ

UB 18DD

Clear Visibility for Outdoor Night Work

HIKOKI



Adjustable from 1,000lm to 10,000lm.



Continuous Runtime per Charge*1			
18V Battery	Min. Brightness 1,000lm	Max. Brightness 10,000lm	
3.0Ah	Approx. 5.5h	Approx. 0.6h	
5.0Ah	Approx. 9.0h	Approx. 1.1h	
8.0Ah	Approx. 14.5h	Approx. 1.8h	



